


# SINGLE-PHASE DRY-TYPE POWER TRANSFORMERS

Ref : 6M103-AB-H043



\*Dimensions are expressed in millimeters, mass in kilograms and reserves represent the ventilation space to be kept around the product for good heat dissipation. The drawing is not contractual.

## Notes et options

Options: Adjustment taps, Multi-voltages, Electrostatic screen, Reduced inrush current, Low consumption, Resistance to harmonics, Silent block, caster, Integrated protections, reinforced insulation, Tropicalization, Class II, transformer Factor K5, K7, K9 , High frequencies.

Additional options for the covered versions: Specific color paint, IP21 to IP55, Built-in case with integrated protections, custom housing possible,

Product reference	6M103-AB-H043
Power/Value	10 KVA
IP Indice	IP21
Voltage(s)/Current	400V / 230V
Number of Phases	Single-Phase
Use frequency	50-60Hz
Dimensions (L x I x H)	505 x 480 x 535
Fixings: X x Y x Ø (mm)	180 x (450 - 200) x 10
Weight	70
Standard	IEC 60076-11
Winding material	Aluminium
RoHS compliant	Yes
Eyebolts	Yes
Recommended Electrical Protection Input / Output	DJ D - 40A / DJ C - 40A
Dielectric Input/Output and active/ground	3000V / 3000V
Insulation class	I
Cooling	Air Naturel